

Allround



M22M

from 598 €

- **Exchangeable lens camera** for indoor/outdoor use (IP65)
- **3MEGA-resolution** (QXGA, 2048x1536 pixels)
- Exchangeable lenses from Super Wide-Angle (90°) to tele (15°); optional with C-/CS-Vario connection
- Color sensor 1 lux at 1/60 sec, 0.05 lux at 1 sec exposure time
- Microphone and speaker with full audio functionality (VoIP and SIP telephony with video)
- Universal wall/ceiling mount perfectly covers RJ45 outlets and conceals the cabling
- Internal DVR (16 GB), recording without network load

DualNight



M12D

from 1098 €

- **Dual camera** with brilliant image color quality during the day and highest sensitivity at night thanks to **two separate image sensors for color and B/W**, for indoor and outdoor (IP65)
- **3MEGA-resolution** (QXGA, 2048x1536 pixels)
- Ideal for challenging lighting conditions or IR lighting; 0.1 lux at 1/60 sec, 0.005 lux at 1 sec exposure time
- PIR sensor for motion detection in the dark
- Microphone and speaker with full audio functionality (VoIP and SIP telephony with video)
- Integrated switch functions (1 x signal input, 1 x signal output), RS232
- Internal DVR (16 GB), recording without network load

MonoDome



D22M

from 448 €

- **FixDome camera** for flexible mounting, for indoor and outdoor (IP65)
- **Optional vandalism, On-Wall and In-Ceiling sets**
- **3MEGA-resolution** (QXGA, 2048x1536 pixels)
- Exchangeable lenses from Super Wide-Angle (90°) to tele (15°)
- Color sensor 1 lux at 1/60 sec, 0.05 lux at 1 sec exposure time
- Vandalism set consists of stainless steel ring (polished, matt, powder-coated) and reinforced dome
- On-Wall set features concealed cabling and space for expansion modules (batteries, UMTS, WiFi, etc.)
- Outdoor wall mount (IP65) with space for expansion modules
- Internal DVR (16 GB), recording without network load

DualDome



D12D

from 998 €

- **DualDome camera** with **two individually positionable image sensors**, for indoor and outdoor (IP65)
- Simultaneous monitoring of different room areas using two separately directionable lenses
- **3MEGA-resolution** (QXGA, 2048x1536 pixels)
- 180° panorama
- PIR sensor for motion detection in the dark
- Microphone and speaker with full audio functionality (VoIP and SIP telephony with video)
- Integrated switch functions (2 x signal input, 2 x signal output), RS232
- Internal DVR (16 GB), recording without network load

Hemispheric



Q22M

from 498 €

- **Hemispheric camera with 360° allround view** for complete room monitoring, for indoor and outdoor (IP65)
- Without mechanically moving parts, robust and maintenance free
- Digital, continuous 8x zoom and panning
- Event-controlled **360° recording**, directly in the camera with SD card support
- Alarm functions, speaker and microphone installed
- Perfect design with low installation height for in-ceiling mounting
- Compatible with all D22 accessories
- Internal DVR (16GB), recording without network load

HiRes Video Innovations

The German company MOBOTIX AG is known as the leading pioneer in network camera technology and its decentralized concept has made high-resolution video systems cost efficient.

MOBOTIX AG • D-67657 Kaiserslautern • Tel: +49-631-3033-103 • Fax: +49-631-3033-190 • sales@mobotix.com



Model: M22M-IT-D22
Indoor/Outdoor: In/Outdoor, weatherproof, -30°...+60°C
Lenses: (eq. 35mm) Super Wide Angle (22mm, 90°, F 2.0)
Resolution: VGA (640x480 pixels), color
Pan/Tilt/Zoom: ./.
Frame Rate (Mono): 30 fps VGA • 30 fps CIF
Sensitivity: 1 lux (t=1/60sec) • 0,05 lux (t=1/1sec)
Interfaces: Ethernet 10/100 Mbps
Internal DVR: up to 16 GB via USB
Audio/Telephony: bidirectional, VoIP, IP-Telephony
Power Sup. • In/Out: PoE or MX30V • via ExtIO
Software Features: FTP, E-Mail, video alarm management, video motion, Multiview, event search
Arming • Triggering: 365 day schedule • multiple events
External Storage: up to 1 Terabyte on PC/Server/NAS

Prices: 598 EUR (MX-M22M-IT-D22)



Model: M22M-Sec
Indoor/Outdoor: In/Outdoor, weatherproof, -30°...+60°C
Lenses: (eq. 35mm) Super Wide Angle (22mm, 90°, F 2.0), 32mm, 43mm, 65mm, 135mm
Resolution: 3MEGA (2048x1536 pixels), color
Pan/Tilt/Zoom: continuous 8x zoom & pan/tilt (digital)
Frame Rate (Mono): 30 fps VGA • 30 fps CIF • 10 fps Mega
Sensitivity: 1 lux (t=1/60sec) • 0,05 lux (t=1/1sec)
Interfaces: Ethernet 10/100 Mbps
Internal DVR: up to 16 GB via USB
Audio/Telephony: bidirectional, VoIP, IP-Telephony
Power Sup. • In/Out: PoE or MX30V • via ExtIO
Software Features: FTP, E-Mail, video alarm management, video motion, Multiview, event search
Arming • Triggering: 365 day schedule • multiple events
External Storage: up to 1 Terabyte on PC/Server/NAS

Prices: 798 EUR (MX-M22M-Sec)



Model: M22M-Sec-Night
Indoor/Outdoor: In/Outdoor, weatherproof, -30°...+60°C
Lenses: (eq. 35mm) Super Wide Angle (22mm, 90°, F 2.0), 32mm, 43mm, 65mm, 135mm
Resolution: MEGA (1280x960 pixels), B/W
Pan/Tilt/Zoom: continuous 8x zoom & pan/tilt (digital)
Frame Rate (Mono): 30 fps VGA • 30 fps CIF • 10 fps Mega
Sensitivity: 0,1 lux (t=1/60sec) • 0,005 lux (t=1/1sec)
Interfaces: Ethernet 10/100 Mbps
Internal DVR: up to 16 GB via USB
Audio/Telephony: bidirectional, VoIP, IP-Telephony
Power Sup. • In/Out: PoE or MX30V • via ExtIO
Software Features: FTP, E-Mail, video alarm management, video motion, Multiview, event search
Arming • Triggering: 365 day schedule • multiple events
External Storage: up to 1 Terabyte on PC/Server/NAS

Prices: 798 EUR (MX-M22M-Sec-Night)



Model: M22M-Sec-CSVario
Indoor/Outdoor: In/Outdoor, weatherproof, -30°...+60°C
Lenses: (eq. 35mm) CS-Mount Vario 24-54 (24 bis 54mm)
Resolution: F 1.6-2.3
Resolution: 3MEGA (2048x1536 pixels), color
Pan/Tilt/Zoom: continuous 8x zoom & pan/tilt (digital)
Frame Rate (Mono): 30 fps VGA • 30 fps CIF • 10 fps Mega
Sensitivity: 1 lux (t=1/60sec) • 0,05 lux (t=1/1sec)
Interfaces: Ethernet 10/100 Mbps
Internal DVR: up to 16 GB via USB
Audio/Telephony: bidirectional, VoIP, IP-Telephony
Power Sup. • In/Out: PoE or MX30V • via ExtIO
Software Features: FTP, E-Mail, video alarm management, video motion, Multiview, event search
Arming • Triggering: 365 day schedule • multiple events
External Storage: up to 1 Terabyte on PC/Server/NAS

Prices: 998 EUR (MX-M22M-Sec-CSVario)



NEW Internal flash recording

Model: M22M-Sec-R8
Indoor/Outdoor: In/Outdoor, weatherproof, -30°...+60°C
Lenses: (eq. 35mm) Super Wide Angle (22mm, 90°, F 2.0), 32mm, 43mm, 65mm, 135mm
Resolution: 3MEGA (2048x1536 pixels), color
Pan/Tilt/Zoom: continuous 8x zoom & pan/tilt (digital)
Frame Rate (Mono): 30 fps VGA • 30 fps CIF • 10 fps Mega
Sensitivity: 1 lux (t=1/60sec) • 0,05 lux (t=1/1sec)
Interfaces: Ethernet 10/100 Mbps
Internal DVR: 8 GB CF-card installed
Audio/Telephony: bidirectional, VoIP, IP-Telephony
Power Sup. • In/Out: PoE or MX30V • via ExtIO
Software Features: FTP, E-Mail, video alarm management, video motion, Multiview, event search
Arming • Triggering: 365 day schedule • multiple events
External Storage: up to 1 Terabyte on PC/Server/NAS

Prices: 998 EUR (MX-M22M-Sec-R8)



Model: M12M-Web-D43
Indoor/Outdoor: In/Outdoor, weatherproof, -30°...+60°C
Lenses: (eq. 35mm) Wide-angle only (43mm, F 2.0) no other lens available
Resolution: 3MEGA (2048x1536 pixels), color
Pan/Tilt/Zoom: continuous 8x zoom & pan/tilt (digital)
Frame Rate (Mono): 30 fps VGA • 30 fps CIF • 10 fps Mega
Sensitivity: 1 lux (t=1/60sec) • 0,05 lux (t=1/1sec)
Interfaces: ISDN, Ethernet 10/100 Mbps
Internal DVR: ./.
Audio/Telephony: ./.
Power Sup. • In/Out: PoE oder MX30V • ./.
Software Features: Logo generator, FTP, E-Mail
Arming • Triggering: 7 day schedule • multiple events
External Storage: FTP, triggered by events/time schedule

Prices: 798 EUR (MX-M12M-Web-D43)



Model: M12D-IT-DNight-D43N43
Indoor/Outdoor: Dual lens outdoor, -30°...+60°C
Lenses: (eq. 35mm) 2 Wide-angle (43mm, F 2.0), DNight: automatic Day/Night switching
Resolution: 2 x VGA (je 640x480 pixels), color & B/W
Pan/Tilt/Zoom: ./.
Frame Rate (Mono): 30 fps VGA • 30 fps CIF
Sensitivity: 0,1 lux (t=1/60sec) • 0,005 lux (t=1/1sec)
Interfaces: ISDN, Ethernet 10/100 Mbps, RS232
Internal DVR: up to 16 GB with SD card
Audio/Telephony: bidirectional, VoIP, IP-Telephony
Power Sup. • In/Out: PoE oder MX30V • 1xIN, 1xOUT
Software Features: FTP, E-Mail, video alarm management, video motion, Multiview, event search
Arming • Triggering: 365 day schedule • multiple events
External Storage: up to 1 Terabyte on PC/Server/NAS

Prices: 1098 EUR (MX-M12D-IT-DNight-D43N43)



Model: M12D-Sec-D22D135
Indoor/Outdoor: Dual lens outdoor, -30°...+60°C
Lenses: (eq. 35mm) Super Wide Angle (22mm, 90°, F 2.0), tele (135mm, F 2.5)
Resolution: 2 x 3MEGA (je 2048x1536 pixels), color
Pan/Tilt/Zoom: continuous 8x zoom & pan/tilt (digital)
Frame Rate (Mono): 30 fps VGA • 30 fps CIF • 10 fps Mega
Sensitivity: 1 lux (t=1/60sec) • 0,05 lux (t=1/1sec)
Interfaces: ISDN, Ethernet 10/100 Mbps, RS232
Internal DVR: up to 16 GB with SD card
Audio/Telephony: bidirectional, VoIP, IP-Telephony
Power Sup. • In/Out: PoE oder MX30V • 1xIN, 1xOUT
Software Features: FTP, E-Mail, video alarm management, video motion, Multiview, event search
Arming • Triggering: 365 day schedule • multiple events
External Storage: up to 1 Terabyte on PC/Server/NAS

Prices: 1248 EUR (MX-M12D-Sec-D22D135)



Model: M12D-Sec-DNight-D43N43
Indoor/Outdoor: Dual lens outdoor, -30°...+60°C
Lenses: (eq. 35mm) 2 Wide-angle (43mm, F 2.0), DNight: automatic Day/Night switching
Resolution: 1 x 3MEGA (2048x1536 pixels), color
Resolution: 1 x MEGA (1280x960 pixels), B/W
Pan/Tilt/Zoom: continuous 8x zoom & pan/tilt (digital)
Frame Rate (Mono): 30 fps VGA • 30 fps CIF • 10 fps Mega
Sensitivity: 0,1 lux (t=1/60sec) • 0,005 lux (t=1/1sec)
Interfaces: ISDN, Ethernet 10/100 Mbps, RS232
Internal DVR: up to 16 GB with SD card
Audio/Telephony: bidirectional, VoIP, IP-Telephony
Power Sup. • In/Out: PoE oder MX30V • 1xIN, 1xOUT
Software Features: FTP, E-Mail, video alarm management, video motion, Multiview, event search
Arming • Triggering: 365 day schedule • multiple events
External Storage: up to 1 Terabyte on PC/Server/NAS

Prices: 1248 EUR (MX-M12D-Sec-DNight-D43N43)



Model: M12D-Sec-DNight-D22N22
Indoor/Outdoor: Dual lens outdoor, -30°...+60°C
Lenses: (eq. 35mm) 2 Wide-angle (43mm, F 2.0), DNight: automatic Day/Night switching
Resolution: 1 x 3MEGA (2048x1536 pixels), color
Resolution: 1 x MEGA (1280x960 pixels), B/W
Pan/Tilt/Zoom: continuous 8x zoom & pan/tilt (digital)
Frame Rate (Mono): 30 fps VGA • 30 fps CIF • 10 fps Mega
Sensitivity: 0,1 lux (t=1/60sec) • 0,005 lux (t=1/1sec)
Interfaces: ISDN, Ethernet 10/100 Mbps, RS232
Internal DVR: up to 16 GB with SD card
Audio/Telephony: bidirectional, VoIP, IP-Telephony
Power Sup. • In/Out: PoE oder MX30V • 1xIN, 1xOUT
Software Features: FTP, E-Mail, video alarm management, video motion, Multiview, event search
Arming • Triggering: 365 day schedule • multiple events
External Storage: up to 1 Terabyte on PC/Server/NAS

Prices: 1348 EUR (MX-M12D-Sec-DNight-D22N22)



NEW Internal flash recording

Model: M12D-Sec-R8
Indoor/Outdoor: Dual lens outdoor, -30°...+60°C
Lenses: (eq. 35mm) Super Wide Angle (22mm, 90°, F 2.0), 43mm, 135mm
Resolution: 1 x 3MEGA (2048x1536 pixels), color
Resolution: 1 x MEGA (1280x960 pixels), B/W
Pan/Tilt/Zoom: continuous 8x zoom & pan/tilt (digital)
Frame Rate (Mono): 30 fps VGA • 30 fps CIF • 10 fps Mega
Sensitivity: 0,1 lux (t=1/60sec) • 0,005 lux (t=1/1sec)
Interfaces: ISDN, Ethernet 10/100 Mbps, RS232
Internal DVR: 8 GB CF-card installed
Audio/Telephony: bidirectional, VoIP, IP-Telephony
Power Sup. • In/Out: PoE oder MX30V • 1xIN, 1xOUT
Software Features: FTP, E-Mail, video alarm management, video motion, Multiview, event search
Arming • Triggering: 365 day schedule • multiple events
External Storage: up to 1 Terabyte on PC/Server/NAS

Prices: from 1498 EUR (MX-M12D-Sec-R8)

MOBOTIX HiRes IP Cameras 2008

- 3 -



The HiRes Video Company



Model: D22Mi-Basic-D22
Indoor/Outdoor: Indoor, IP54, -30°...+50°C
Lenses: (eq. 35mm) Super Wide Angle (22mm, 90°, F 2.0)
Resolution: VGA (640x480 pixels), color
Pan/Tilt/Zoom: ./.
Frame Rate (Mono): 16 fps VGA • 16 fps CIF
Sensitivity: 1 lux (t=1/60sec) • 0,05 lux (t=1/1sec)
Interfaces: Ethernet 10/100 Mbps
Internal DVR: ./.
Audio/Telephony: ./.
Power Sup. • In/Out: PoE oder MX30V • ./.
Software Features: FTP, E-Mail, video alarm management, video motion, Multiview, event search
Arming • Triggering: ./.
External Storage: ./.

Prices: 448 EUR (MX-D22Mi-Basic-D22)



Model: D22M-IT-D22
Indoor/Outdoor: In/Outdoor, weatherproof, -30°...+60°C
Lenses: (eq. 35mm) Super Wide Angle (22mm, 90°, F 2.0)
Resolution: VGA (640x480 pixels), color
Pan/Tilt/Zoom: ./.
Frame Rate (Mono): 30 fps VGA • 30 fps CIF
Sensitivity: 1 lux (t=1/60sec) • 0,05 lux (t=1/1sec)
Interfaces: Ethernet 10/100 Mbps, USB, ext. Audio up to 16 GB with SD card
Internal DVR: up to 16 GB with SD card
Audio/Telephony: bidirectional, VoIP, IP-Telephony
Power Sup. • In/Out: PoE oder MX30V • via Mini-USB
Software Features: FTP, E-Mail, video alarm management, video motion, Multiview, event search
Arming • Triggering: 365 day schedule • multiple events
External Storage: up to 1 Terabyte on PC/Server/NAS

Prices: 548 EUR (MX-D22M-IT-D22)



Model: D22M-Sec
Indoor/Outdoor: In/Outdoor, weatherproof, -30°...+60°C
Lenses: (eq. 35mm) Super Wide Angle (22mm, 90°, F 2.0), 32mm, 43mm, 65mm, 135mm
Resolution: 3MEGA (2048x1536 pixels), color
Pan/Tilt/Zoom: continuous 8x zoom & pan/tilt (digital)
Frame Rate (Mono): 30 fps VGA • 30 fps CIF • 10 fps Mega
Sensitivity: 1 lux (t=1/60sec) • 0,05 lux (t=1/1sec)
Interfaces: Ethernet 10/100 Mbps, USB, ext. Audio up to 16 GB with SD card
Internal DVR: up to 16 GB with SD card
Audio/Telephony: bidirectional, VoIP, IP-Telephony
Power Sup. • In/Out: PoE oder MX30V • via Mini-USB
Software Features: FTP, E-Mail, video alarm management, video motion, Multiview, event search
Arming • Triggering: 365 day schedule • multiple events
External Storage: up to 1 Terabyte on PC/Server/NAS

Prices: 748 EUR (MX-D22M-Sec)



Model: D22M-Sec-Night
Indoor/Outdoor: In/Outdoor, weatherproof, -30°...+60°C
Lenses: (eq. 35mm) Super Wide Angle (22mm, 90°, F 2.0), 32mm, 43mm, 65mm, 135mm
Resolution: MEGA (1280x960 pixels), B/W
Pan/Tilt/Zoom: continuous 8x zoom & pan/tilt (digital)
Frame Rate (Mono): 30 fps VGA • 30 fps CIF • 10 fps Mega
Sensitivity: 0,1 lux (t=1/60sec) • 0,005 lux (t=1/1sec)
Interfaces: Ethernet 10/100 Mbps, USB, ext. Audio up to 16 GB with SD card
Internal DVR: up to 16 GB with SD card
Audio/Telephony: bidirectional, VoIP, IP-Telephony
Power Sup. • In/Out: PoE oder MX30V • via Mini-USB
Software Features: FTP, E-Mail, video alarm management, video motion, Multiview, event search
Arming • Triggering: 365 day schedule • multiple events
External Storage: up to 1 Terabyte on PC/Server/NAS

Prices: 748 EUR (MX-D22M-Sec-Night)



Model: Q22-Basic
Indoor/Outdoor: Indoor, IP54, -30°...+50°C
Lenses: (eq. 35mm) Hemispheric (11mm), Super Wide Angle (22mm, 90°, F 2.0)
Resolution: VGA (640x480 pixels), color
Pan/Tilt/Zoom: digital PTZ via MxControlCenter
Frame Rate (Mono): 16 fps VGA • 16 fps CIF
Sensitivity: 1 lux (t=1/60sec) • 0,05 lux (t=1/1sec)
Interfaces: Ethernet 10/100 Mbps
Internal DVR: ./.
Audio/Telephony: ./.
Power Sup. • In/Out: PoE oder MX30V
Software Features: distortion correction in MxCC, FTP, E-Mail, video alarm manag., multiview
Arming • Triggering: ./.
External Storage: ./.

Prices: 498 EUR (MX-Q22Mi-Basic-D11)



Model: Q22-Sec
Indoor/Outdoor: In/Outdoor, weatherproof, -30°...+60°C
Lenses: (eq. 35mm) Hemispheric (11mm), Super Wide Angle (22mm, 90°, F 2.0)
Resolution: 3MEGA (2048x1536 pixels), color
Pan/Tilt/Zoom: continuous 8x zoom & pan/tilt (digital)
Frame Rate (Mono): 30 fps VGA • 10 fps Mega • 4 fps 3MEGA
Sensitivity: 1 lux (t=1/60sec) • 0,05 lux (t=1/1sec)
Interfaces: Ethernet 10/100 Mbps, USB, ext. Audio up to 16 GB with SD card
Internal DVR: up to 16 GB with SD card
Audio/Telephony: bidirectional, VoIP, IP-Telephony
Power Sup. • In/Out: PoE oder MX30V • 2x In, 1x Out
Software Features: distortion correction in the camera, FTP, E-Mail, video alarm manag.
Arming • Triggering: 365 day schedule • multiple events
External Storage: up to 1 Terabyte on PC/Server/NAS

Prices: 648 EUR (MX-Q22M-Sec-D11)



Model: D12Di-IT
Indoor/Outdoor: Dual lens indoor, IP54, -30°...+60°C
Lenses: (eq. 35mm) Super Wide Angle (22mm, 90°, F 2.0)
Resolution: 2 x VGA (je 640x480), color & B/W
Pan/Tilt/Zoom: ./.
Frame Rate (Mono): 30 fps VGA • 30 fps CIF
Sensitivity: 1 lux (t=1/60sec) • 0,05 lux (t=1/1sec)
Interfaces: ISDN, Ethernet 10/100 Mbps, RS232
Internal DVR: up to 16 GB with SD card
Audio/Telephony: bidirectional, VoIP, IP-Telephony
Power Sup. • In/Out: PoE oder MX30V • 1xIN, 1xOUT
Software Features: FTP, E-Mail, video alarm management, video motion, Multiview, event search
Arming • Triggering: 365 day schedule • multiple events
External Storage: up to 1 Terabyte on PC/Server/NAS

Prices: 998 EUR (MX-D12Di-IT)



Model: D12Di-Sec
Indoor/Outdoor: Dual lens indoor, IP54, -30°...+60°C
Lenses: (eq. 35mm) Super Wide Angle (22mm, 90°, F 2.0), 32mm, 43mm, 65mm, 135mm
Resolution: 1 x 3MEGA (2048x1536 pixels), color
Pan/Tilt/Zoom: continuous 8x zoom & pan/tilt (digital)
Frame Rate (Mono): 30 fps VGA • 30 fps CIF • 10 fps Mega
Sensitivity: 1 lux (t=1/60sec) • 0,05 lux (t=1/1sec)
Interfaces: ISDN, Ethernet 10/100 Mbps, RS232
Internal DVR: up to 16 GB with SD card
Audio/Telephony: bidirectional, VoIP, IP-Telephony
Power Sup. • In/Out: PoE oder MX30V • 1xIN, 1xOUT
Software Features: FTP, E-Mail, video alarm management, video motion, Multiview, event search
Arming • Triggering: 365 day schedule • multiple events
External Storage: up to 1 Terabyte on PC/Server/NAS

Prices: 1248 EUR (MX-D12Di-Sec)



Model: D12Di-Sec-180°
Indoor/Outdoor: Dual lens indoor, IP54, -30°...+60°C
Lenses: (eq. 35mm) Super Wide Angle (22mm, 90°, F 2.0), 32mm, 43mm, 65mm, 135mm
Resolution: 1 x 3MEGA (2048x1536 pixels), color
Pan/Tilt/Zoom: continuous 8x zoom & pan/tilt (digital)
Frame Rate (Mono): 30 fps VGA • 30 fps CIF • 10 fps Mega
Sensitivity: 1 lux (t=1/60sec) • 0,05 lux (t=1/1sec)
Interfaces: ISDN, Ethernet 10/100 Mbps, RS232
Internal DVR: up to 16 GB with SD card
Audio/Telephony: bidirectional, VoIP, IP-Telephony
Power Sup. • In/Out: PoE oder MX30V • 1xIN, 1xOUT
Software Features: FTP, E-Mail, video alarm management, video motion, Multiview, event search
Arming • Triggering: 365 day schedule • multiple events
External Storage: up to 1 Terabyte on PC/Server/NAS

Prices: 1248 EUR (MX-D12Di-Sec-180°)

MxControlCenter for Windows Client:
 High performance with 40 smooth video streams live/stored, integration of analog and digital PTZ cameras with joystick control, alarm management, event search



Prices: free Download (mobotix.com)

Lens options	L22 Day	L22 Night	L32 Day	L32 Night	L43 Day	L43 Night	L65 Day	L65 Night	L135 Day	L135 Night
	• Standard delivery (incl.) • Optional lens (excl.)									
M22M-IT-D22	•	-	•	-	•	-	•	-	•	-
M22M-Sec	•	-	•	-	•	-	•	-	•	-
M22M-Sec-Night	-	•	-	•	-	•	-	•	-	•
M12M-Web-D43	-	-	-	-	•	-	-	-	-	-
M12D-IT-DNight-D43N43	-	-	-	-	•	•	-	-	-	-
M12D-Sec-D22D135	•	-	-	-	-	-	-	-	•	-
M12D-Sec-DNight-D22N22	•	•	-	-	-	-	-	-	-	-
M12D-Sec-DNight-D43N43	-	-	-	-	•	•	-	-	-	-
D12Di-IT/D12Di-Sec	•	•	•	•	•	•	•	•	•	•
D22Mi-Basic-D22	•	-	•	-	•	-	•	-	•	-
D22M-IT-D22	•	-	•	-	•	-	•	-	•	-
D22M-IT-Night-N22	-	•	-	•	-	•	-	•	-	•
D22M-Sec	•	-	•	-	•	-	•	-	•	-
D22M-Sec-Night	-	•	-	•	-	•	-	•	-	•

Prices ex works Germany • Excl. VAT and country specific customs taxes • Subject to change without notice

MOBOTIX HiRes IP Camera Accessories 2008

- 4 -



The HiRes Video Company

M12/M22 Access.



Part Name: SecureFlex-Wall-/Ceiling Mount
Description:

- protected concealed cabling
- ± 90° right/left pivoting
- 70° down tilt
- covers RJ45 wall outlets
- compatible with M1/M10/M12-cameras

Prices: 48 EUR (MX-WH-SecureFlex)



M12/M22-Pole Mount

- 3mm stainless steel, white
- mast or pole mounting
- Pole circumference from 60 to 180mm
- 2 x metal mounting bands, fittings and grommet included

78 EUR (MX-MH-SecureFlex-ESWS)



Cam-IO-PoE / AC / ACplus

- Interface for external sensors and equipment (door contact, light, etc.)
- 2xRelais-Out, 2xInput, backup, audio
- Power supply via network / 230V / 230V battery buffered

from 298 EUR (MX-CAMIO)

D12 Accessories



D12 Vandalism Set

- Reinforced dome (3mm Polyc.)
- Stainless steel vandalism ring (matt, polished or white, silver, black powder-coated)

148 EUR (MX-D12-Vandal)



D12 Wall Mount

- Weatherproof (IP65) for D12D-Dome
- robust and UV resistant PBT-30GF
- concealed cabling
- covers RJ45 wall outlets
- possible to fit WLAN or GSM/GPRS equipment inside housing

148 EUR (MX-WH-Dome)



D12 Pole Mount

- 3mm stainless steel, powder-coated
- Pole diam.: 60 to 180mm
- Incl. mounting supplies

98 EUR (MX-MH-Dome-ESWS)

D22 Accessories



D22 Vandalism Set

- Reinforced dome (3mm Polyc.)
- Stainless steel vandalism ring (matt, polished or white, silver, black powder-coated)

98 EUR (MX-D22M-Vandal)



D22 On-Wall Set

- On-wall mount incl. mounting parts
- Concealed cabling
- Ø 165x37mm/6.5x1.5in
- excluding camera

98 EUR (MX-D22M-OPT-AP)



D22 In-Ceiling Set

- In-ceiling set incl. mounting parts
- Easy mounting from front
- Ø 150mm/5.9in diameter
- excluding camera

98 EUR (MX-D22M-OPT-IC)



D22 Wall Mount

- Weather protection (IP65) for D22
- Covers RJ45 wall outlets
- Space for expansion modules (WiFi)

98 EUR (MX-D22M-OPT-WH)



D22 Pole Mount

- 3mm stainless steel, powder-coated
- Pole diam.: 60 to 180mm
- Incl. mounting supplies

98 EUR (MX-D22M-OPT-MH)



Accessories All Cams



Part Name: Network Power Adapter Set
Description: Power supply via network cabling
 All camera models (MX30V)

98 EUR (MX-NPA-Set)



Network Power Box for 4 cameras
 Power supply for DIN rails
 All camera models (MX30V)

398 EUR (MX-NPR-4)



Network Power Rack (8/20 cameras)
 Power supply via network cabling
 All camera models (MX30V)

from 948 EUR (MX-NPR-8 / MX-NPR-20)



M12-DevKit

- M12 main board incl. sound module for connecting up to 2 cameras
- without housing for concealed installation
- housing available separately

from 948 EUR (MX-M12-DevKit-Board)



ExItO

- Each with 2 In- and Output contacts 8-24V
- Microphone with adjustable volume control, speaker, status LEDs
- USB interface
- Temperature sensor, 2 buttons

198 EUR (MX-ExItO)



L22 Super Wide Angle (90° x 67°)



L32 Wide Angle (60° x 45°)



L43 Wide Angle (45° x 34°)



L65 Tele (31° x 23°)



L135 Tele (15° x 11°)



V24-54 CSVario*



Lenses

* M22M special model

Prices ex works Germany • Excl. VAT and country specific customs taxes • Subject to change without notice